


SPECIALS

Deep Brushed



Packaging

Boards per pack: m² per pack: Weight per pack: Broken lenghts per pack:

Dimensions

Length: Width: Thickness (total): Top layer: 25% minimal 60 cm length 190 cm 19 cm

8 boards

2,89 m²

24 kg

15 mm

3.5-4.0 mm

Dimensional tolerances according to EN13489

| Length: | 0,20% |
|--------------------------------------|------------------------|
| Width: | 0,2 mm |
| Thickness: | Total: 15 mm ± 0,2 mm |
| Top layer: | 3,5-4,0 mm |
| Height difference between the panels | : ≤0,2 mm |
| Squareness: | ≤0.2% across the width |
| Cup: | ≤0.2% across the width |
| Spring: | ≤0.1% over the length |
| Bend: | ≤1% over the length |

Other Specifications

Formaldehyde emission: Insulation value: Brinell hardness:

Additional specifications

Bevel: Construction: Moisture content: Locking system:

Instructions and Maintenance

Oil immediately after installation. Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).

E1

R=0,115m2 k/w

Average HB 3.7

Rounded

3-layerd

7% +/- 2%

Tongue and groove

