

MANSION DRYBACK

Mansion Dryback Natural Oak

1209788

153,2 × 23,7 cm
2,5/0,55 mm

CE
EN 14342-05

25 years
Solidfloor™
guarantee



Packaging

| | |
|------------------------------|---------------------|
| Boards per pack: | 10 boards |
| m ² per pack: | 3,62 m ² |
| Weight per pack: | 15,56 kg |
| Number of packs on a pallet: | 36 |

Dimensions

| | |
|------------|-------------------------------------|
| Length: | 153,2 cm |
| Width: | 23,7 cm |
| Thickness: | Total: 2.5 mm Top layer: 0.55 mm |

Use

| | |
|-------------------------------------|--|
| Usage class: | 23 intensive domestic residential use 33 intensive commercial use |
| Floor heating (EN12524): | Yes, up to 27C° |
| Suitable for office chairs?: | Yes |
| Resistant to chemicals? (EN 423): | Yes, good |
| Acoustic reduction of impact sound: | 3dB |

Specifications

| | |
|-------------------------------------|--------------------------|
| Lightfastness (ISO 105-B02): | >6 |
| Abrasion resistance (EN 660-2): | Group T |
| Heat transfer coefficient: | R=0,02m ² k/w |
| Antistatic: | <2kV |
| Residual indentation (ISO 24343-1): | <0,05 mm |
| Dimensional stability: | <0.2% |
| Slip resistance (DIN 51130): | R9 |
| Repetition factor: | 4 |
| Locking system: | N.a. |
| Bevel: | 4-sided, micro bevel |
| Fire class: | Bfl-S1 |
| VOC Emission: | A+ |

Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit www.solidfloor.com for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.